

Super Agri - SA - the ultimate for tough conditions



Simply tougher

The Super Agri is the ultimate direct electric hot water cylinder, with distinctive design features. Made to withstand the toughest of exterior environments with outer casing in stainless steel, the Super Agri is ideal for agricultural use, but is also a stylish alternative to the modern home. Ease of installation combined with all connections hidden makes the Agri fit seamlessly in every environment. Based on OSO's experience through 80 years and with more than 3 million units sold, the Super series is the new benchmark.

The Super Agri utilizes a special electric heater to prevent lime-scale issues. It also has a separate draw-off connection, for un-mixed hot water up to 90°C when required. The insulated, easily removable top lid hides all connections to the cylinder. The factory fitted mixing valve provides adjustable hot water temperature, non-return and stop valve. Duplex stainless steel makes the Super series extremely lightweight and space-efficient for easy handling and installation. Low heat loss is provided by OSO ECO Foam, with impressive key figures for GWP of 1 (Global Warming Potential) and ODP of 0 (Ozone Depletion Potential.) Integrated, adjustable feet, as well as channels for drainpipe and electric connection.

The Super Agri can be heated up to 90°C, with water drawn off either through the separate connection, or through the mixing valve and temperature blended down.

+ KEY ADVANTAGES

- Pioneering design features with all connections hidden and insulated
- Duplex stainless steel for lightweight handling and aggressive environments
- Stainless steel outer casing and separate connection for high temp. hot water
- 10 year warranty on the stainless steel inner cylinder & OSO ECO Foam insulation

Technical data

Product - vol. - kW/phxV	Product capacity	Dia x H mm	Conn. cw/hw	Usable hot water 40°C - ltr.	Hot water / hour 40°C - ltr.	Heat-up time 15-75°C - hrs.	Heat loss 24 hrs. - kWh	Kg	M³	Prod.no.
SA 200 - 3 / 3x400V	4,0 persons	ø580 x 1260 H	½" / ø15	370	85	4,6	1,90	39	0,45	8 000 832
SA 300 - 3 / 3x400V	5.5 persons	ø580 x 1710 H	½" / ø15	535	85	6,7	2,30	51	0,60	8 000 834